

Amendments to the Claims:

Claims 2, 5, 8 – 11, 15 – 21, 27 – 39, 41 – 42, and 49 – 50 are original. Claims 1, 3 – 4,
6 – 7, 12 – 14, 23 – 26, 45, and 48 are previously presented. Claims 40, 44, and 46 – 47 are
currently amended. Claims 22, 43 and 51 are cancelled. No new matter is introduced by these
5 amendments.

Listing of Claims:

Claim 1 (previously presented): A method for changing a selectable divisor
in a programmable frequency divider, the frequency divider
10 comprising a plurality of cascaded cells, the method comprising:

- (a) providing a plurality of divisor signals;
- (b) selectively switching each of the plurality of cells to a
divide-by-two or a divide-by-three mode according to the
plurality of divisor signals; and
- 15 (c) synchronously resetting at least a part of the plurality of cells
in response to a reset signal by returning each cell into a
predetermined respective state.

Claim 2 (original): The method of claim 1, wherein step (c) further
20 comprises synchronously resetting all of the plurality of cells.

Claim 3 (previously presented): The method of claim 1, wherein the
method further comprises step (d):
reloading the plurality of divisor signals to the plurality of cells in
25 response to a reload signal.

Claim 4 (previously presented): The method of claim 3, wherein step (d)

further comprises synchronously reloading the plurality of divisor signals to the plurality of cells.

5 Claim 5 (original): The method of claim 3, wherein the plurality of cells comprises at least one cell having a bypass mode, the method further comprising:
determining whether to bypass at least a part of the at least one cell having a bypass mode according to the plurality of divisor signals in order to inhibit bypassed cells from performing a
10 frequency-dividing operation.

Claim 6 (previously presented): The method of claim 5, wherein step (d) further comprises synchronously resetting each bypassed cell.

15 Claim 7 (previously presented): The method of claim 5, wherein step (d) further comprises synchronously resetting the plurality of cells.

Claim 8 (original): The method of claim 5, wherein the reloading step further comprises synchronously reloading the corresponding
20 divisor signals to the bypassed cells.

Claim 9 (original): The method of claim 5, wherein the reloading step further comprises synchronously reloading the plurality of divisor signals to the plurality of cells.
25

Claim 10 (original): The method of claim 5, further comprising:
utilizing a control circuit coupled to the bypassed cells for providing a reset signal.

Claim 11 (original): The method of claim 5, further comprising:
utilizing a control circuit coupled to each of the plurality of cells
for providing a reset signal.

5

Claim 12 (previously presented): The method of claim 11, wherein step (d)
further comprises utilizing the control circuit to output the reset
signal to the bypassed cells and a cell having a bypass mode which
is prior to the bypassed cells, the reset signal being output after the
10 bypassed cells are loaded with the corresponding divisor signals.

Claim 13 (previously presented): The method of claim 5, wherein step (d)
further comprises bypassing a cell having a bypass mode when
divisor signals input to the cell and each of its subsequent cells
15 having a bypass mode are logic 0.

Claim 14 (previously presented): A programmable frequency divider for
dividing the frequency of a source signal according to a
selectable divisor which is obtained based on a plurality of
20 divisor signals and outputting a result signal having a divided
frequency, the programmable frequency divider comprising:
at least one cell of a first type being switchable between
divide-by-two and divide-by-three modes having a first input
node (Fi), a second input node (Mi), a third input node (Di), a
25 fourth input node (Rs), a first output node (Fo), and a second
output node (Mo), the third input node (Di) being used for
receiving a corresponding divisor signal, the fourth input node
(Rs) being used for receiving a reset signal from a control

5 circuit to synchronously reset the cell of the first type;
wherein if the programmable frequency divider comprising a
plurality of cells of the first type, the cells of the first type
being cascaded with each other, the first output node (Fo)
being coupled to a first input node (Fi) of a subsequent cell of
the first type, the second input node (Mi) being coupled to a
second output node (Mo) of the subsequent cell of the first
type, a first input node (Fi) of a first cell of the first type
being coupled to the source signal, and a second input node
10 (Mi) of a last cell of the first type being set to logic 1; the
programmable frequency divider synchronously resets all of
the cells of the first type according to the reset signal in order
to selectively switch each cell of the first type to perform a
divide-by-two or divide-by-three operation according to the
15 respective divisor signal after the cell is reset, and the second
output node (Mo) or the first output node (Fo) of the last cell
of the first type outputs the result signal having the divided
frequency.

- 20 Claim 15 (original) The programmable frequency divider of claim 14
wherein each cell of the first type operates such that:
- (a) regardless of the logic level of the second input node (Mi), if
the first output node (Fo) and the third input node (Di) are
both at logic 0, the positive edge of a clock signal of the first
25 input node (Fi) triggers the first output node (Fo) to output a
half frequency signal;
 - (b) if the second input node (Mi) and the third input node (Di) are
both at logic 1 and the first output node (Fo) is at logic 0, the

positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;

- 5 (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and
- 10 (e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal and, additionally, if the second input node (Mi) is at logic 1, the second output node (Mo) outputs a logic 1 signal.

15 Claim 16 (original): The programmable frequency divider of claim 14 wherein each cell of the first type operates such that:

- (a) regardless of the logic level of the second output node (Mo), if the third input node (Di) is at logic 0, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 20 (b) if the second output node (Mo) and the third input node (Di) are both at logic 1, the positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- 25 (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi), if

the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and

- (e) if the reset signal received in the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal; and, additionally, if the second input node (Mi) is at logic 1, the second output node (Mo) outputs a logic 1 signal.

Claim 17 (original): The programmable frequency divider of claim 14 further comprising:

a cell of a second type having a bypass mode and being cascaded to the last cell of the first type, the cell of the second type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rs), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input node (Fi) being coupled to a first output node (Fo) of the last cell of the first type, the second input node (Mi) being coupled to Vcc, the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Rs) being used for receiving the reset signal to synchronously reset the second cell, the fifth input node (Ci) being used for receiving the last divisor signal, and the second output node (Mo) being coupled to a second input node (Mi) of the last cell of the first type;

wherein the cell of the second type switches to the divide-by-two or the divide-by-three mode according to the divisor signal received on the third input node (Di) after being synchronously reset, and if the last divisor signal received on the fifth input node (Ci) is at a bypass-mode active state, the

cell of the second type switches to a bypass mode.

Claim 18 (original): The programmable frequency divider of claim 17 wherein each cell of the second type operates such that:

- 5 (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) and the third input node (Di) are both at logic 0, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 10 (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1, the positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a
- 15 one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi),
- 20 if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal;
- (e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal;
- 25 and
- (f) if the signal received on the fifth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1

signal.

Claim 19 (original): The programmable frequency divider of claim 17 further comprising:

5 at least one cell of a third type having a bypass mode and being cascaded between at least one cell of the first type and the cell of the second type, each cell of the third type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rs), a fifth input node (Ci), a first
10 output node (Fo), a second output node (Mo), and a third output node (Co), the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the third type, the third input node (Di)
15 being used for receiving a corresponding divisor signal, the fourth input node (Rs) being used for receiving the reset signal to synchronously reset the third cell, the fifth input node (Ci) being coupled to a third output node (Co) of the subsequent cell and being used for receiving a bypass-mode enabling
20 signal, a first input node (Fi) of a first cell of the third type being coupled to a first output node (Fo) of the last cell of the first type, a second output node (Mo) of the first cell of the third type being coupled to the second input node (Mi) of the last cell of the first type, a first output node (Fo) of a last cell
25 of the third type being coupled to the first input node (Fi) of the cell of the second type, a second input node (Mi) of the last cell of the third type being coupled to the second output node (Mo) of the cell of the second type;

5 wherein each cell of the third type switches to a divide-by-two or divide-by-three mode according to the divisor signal received on the third input node (Di), and if the bypass-mode enabling signal received on the fifth input node (Ci) is at an active state, the cell of the third type switches to a bypass mode.

- Claim 20 (original): The programmable frequency divider of claim 19 wherein each cell of the third type operates such that:
- 10 (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) and the third input node (Di) are both at logic 0, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 15 (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a
- 20 one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- 25 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal;
- (e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal

and the second output node (Mo) outputs a logic 1 signal;
and

(f) if the bypass-mode enabling signal received on the fifth
input node (Ci) is at an active state, the first output node
5 (Fo) outputs a logic 0 signal and the second output node
(Mo) outputs a logic 1 signal.

Claim 21 (original): The programmable frequency divider of claim 14
further comprising a control circuit for providing the reset
10 signal.

Claim 22 (cancelled)

Claim 23 (previously presented): A programmable frequency divider for
15 dividing the frequency of a source signal according to a
selectable divisor which is obtained based on a plurality of
divisor signals and outputting a result signal having a divided
frequency, the programmable frequency divider comprising:
at least one cell of a fourth type being switchable between
20 divide-by-two and divide-by-three modes having a first input
node (Fi), a second input node (Mi), a third input node (Di), a
fourth input node (Rl), a first output node (Fo), and a second
output node (Mo), the third input node (Di) being used for
receiving a corresponding divisor signal, the fourth input node
25 (Rl) being used for receiving a reload signal to synchronously
reload the corresponding divisor signal to the third input node
(Di);
wherein if the programmable frequency divider comprising a

plurality of cells of the fourth type, the cells of the fourth type being cascaded with each other, the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the fourth type, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the fourth type, a first input node (Fi) of a first cell of the fourth type being coupled to the source signal, and a second input node (Mi) of a last cell of the fourth type being set to logic 1; the programmable frequency divider synchronously reloads the corresponding divisor signals to the third input node (Di) of each cell of the fourth type according to the reload signal in order to selectively switch each cell of the fourth type to perform a divide-by-two or divide-by-three operation, and the second output node (Mo) or the first output node (Fo) of the last cell of the fourth type outputs the result signal having the divided frequency; and each cell of the fourth type operates such that:

- (a) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the second input node (Mi) is at logic 1, the first output node (Fo) is at logic 0, and the third input node (Di) is at logic 1 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a

one-third-frequency signal;

(c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi); and

5 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal.

Claim 24 (previously presented): A programmable frequency divider for
10 dividing the frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the programmable frequency divider comprising:
at least one cell of a fourth type being switchable between
15 divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Ri), a first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Ri) being used for receiving a reload signal to synchronously reload the corresponding divisor signal to the third input node (Di);
20 wherein if the programmable frequency divider comprising a plurality of cells of the fourth type, the cells of the fourth type being cascaded with each other, the first output node (Fo)
25 being coupled to a first input node (Fi) of a subsequent cell of the fourth type, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the fourth

type, a first input node (Fi) of a first cell of the fourth type being coupled to the source signal, and a second input node (Mi) of a last cell of the fourth type being set to logic 1; the programmable frequency divider synchronously reloads the corresponding divisor signals to the third input node (Di) of each cell of the fourth type according to the reload signal in order to selectively switch each cell of the fourth type to perform a divide-by-two or divide-by-three operation, the second output node (Mo) or the first output node (Fo) of the last cell of the fourth type outputs the result signal having the divided frequency; and each cell of the fourth type operates such that:

- (a) regardless of the logic level of the second output node (Mo), if the third input node (Di) is at logic 0 when the fourth input node (Ri) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the second output node (Mo) is at logic 1 and the third input node (Di) is at logic 1 when the fourth input node (Ri) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi); and
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output

node (Mo) outputs a logic 0 signal.

Claim 25 (previously presented): A programmable frequency divider for
dividing the frequency of a source signal according to a
5 selectable divisor which is obtained based on a plurality of
divisor signals and outputting a result signal having a divided
frequency, the programmable frequency divider comprising:
at least one cell of a fourth type being switchable between
divide-by-two and divide-by-three modes having a first input
10 node (Fi), a second input node (Mi), a third input node (Di), a
fourth input node (Ri), a first output node (Fo), and a second
output node (Mo), the third input node (Di) being used for
receiving a corresponding divisor signal, the fourth input node
(Ri) being used for receiving a reload signal to synchronously
15 reload the corresponding divisor signal to the third input node
(Di), and the fourth input node (Ri) of each cell of the fourth
type is being coupled to a second output node (Mo) of the last
cell of the fourth type in order to apply the result signal having
the divided frequency to be the reload signal;
20 wherein if the programmable frequency divider comprising a
plurality of cells of the fourth type, the cells of the fourth type
being cascaded with each other, the first output node (Fo)
being coupled to a first input node (Fi) of a subsequent cell of
the fourth type, the second input node (Mi) being coupled to a
25 second output node (Mo) of the subsequent cell of the fourth
type, a first input node (Fi) of a first cell of the fourth type
being coupled to the source signal, and a second input node
(Mi) of a last cell of the fourth type being set to logic 1; the

programmable frequency divider synchronously reloads the corresponding divisor signals to the third input node (Di) of each cell of the fourth type according to the reload signal in order to selectively switch each cell of the fourth type to perform a divide-by-two or divide-by-three operation, and the second output node (Mo) or the first output node (Fo) of the last cell of the fourth type outputs the result signal having the divided frequency.

10 Claim 26 (previously presented): The programmable frequency divider of claim 25 further comprising:

15 a cell of a fifth type having a bypass mode and being cascaded to the last cell of the fourth type, the cell of the fifth type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rl), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input node (Fi) being coupled to a first output node (Fo) of the last cell of the fourth type, the second input node (Mi) being coupled to Vcc, the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Rl) being used for receiving the reload signal to synchronously reload the corresponding divisor signal to the third input node (Di), the fifth input node (Ci) being coupled to the last divisor signal, and the second output node (Mo) being coupled to the second input node (Mi) of the last cell of the fourth type;

25 wherein the reload signal triggers the cell of the fifth type to synchronously reload the corresponding divisor signal to the

third input node (Di) and the cell of the fifth type switches to a divide-by-two or divide-by-three mode according to the divisor signal, and if the last divisor signal received in the fifth input node (Ci) is at a bypass-mode active state, the cell of the fifth type switches to a bypass mode.

Claim 27 (original): The programmable frequency divider of claim 26 wherein each cell of the fifth type operates such that:

- (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and

(e) if the signal received in the fifth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal.

5 Claim 28 (original): The programmable frequency divider of claim 26, wherein the fourth input node (Rl) of the cell of the fifth type is coupled to the second output node (Mo) of the last cell of the fourth type in order to apply the result signal having the divided frequency to be the reload signal.

10

Claim 29 (original): The programmable frequency divider of claim 26, further comprising:

15

at least one cell of a sixth type having a bypass mode and being cascaded between at least one cell of the fourth type and the cell of the fifth type, each cell of the sixth type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rl), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell, the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Rl) being used for receiving the reload signal to

20

25

synchronously reload the the corresponding divisor signal to the third input node (Di), the fifth input node (Ci) being coupled to a third output node (Co) of the subsequent cell and being used for receiving a bypass-mode enabling signal, a first

5 input node (Fi) of a first cell of the sixth type being coupled to the first output node (Fo) of the last cell of the fourth type, a second output node (Mo) of the first cell of the sixth type being coupled to the second input node (Mi) of the last cell of the fourth type, a first output node (Fo) of a last cell of the sixth type being coupled to the first input node (Fi) of the cell of the fifth type, and a second input node (Mi) of the last cell of the sixth type being coupled to the second output node (Mo) of the cell of the fifth type;

10 wherein the reload signal triggers the at least one cell of the sixth type to synchronously reload the corresponding divisor signal to the third input node (Di) and each cell of the sixth type switches to a divide-by-two or divide-by-three mode according to the respective divisor signal, and if the
15 bypass-mode enabling signal received in the fifth input node (Ci) is at an active state, the cell of the sixth type switches to a bypass mode.

20 Claim 30 (original): The programmable frequency divider of claim 29, wherein each cell of the sixth type operates such that:

- 25 (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the first output node (Fo) is at logic 0, the second input

- 5 node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal having the same logic level as the second input node (Mi);
- 10 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and
- (e) if the bypass-mode enabling signal received on the fifth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal.
- 15

Claim 31 (original): The programmable frequency divider of claim 29, wherein the fourth input node (Rl) of each cell of the sixth type is coupled to the second output node (Mo) of the last cell of the fourth type in order to apply the result signal having the divided frequency to be the reload signal.

20

Claim 32 (original): A programmable frequency divider for dividing the frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the programmable frequency divider comprising:

25

at least one cell of a seventh type being switchable between divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rs), a fifth input node (Rl), a first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Rs) being used for receiving a reset signal to synchronously reset the cell of the seventh type, the fifth input node (Rl) being used for receiving a reload signal to synchronously reload the corresponding divisor signal to the third input node (Di);

wherein if the programmable frequency divider comprising a plurality of cells of the seventh type, the cells of the seventh type being cascaded with each other and each cell of the seventh type, the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the seventh type, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the seventh type, a first input node (Fi) of a first cell of the seventh type being coupled to the source signal, and a second input node (Mi) of a last cell of the seventh type being set to logic 1; the programmable frequency divider reloads the corresponding divisor signal to the third input node (Di) of each cell of the seventh type according to the reload signal and resets each cell of the seventh type according to the reset signal in order to selectively switch each cell of the seventh type to perform a divide-by-two or divide-by-three operation according to the respective divisor signal loaded before reset, and the second

output node (Mo) or the first output node (Fo) of the last cell of the seventh type outputs the result signal having the divided frequency.

- 5 Claim 33 (original): The programmable frequency divider of claim 32, wherein each cell of the seventh type operates such that:
- 10 (a) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fifth input node (R1) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 15 (b) if the second input node (Mi) is at logic 1, the first output node (Fo) is at logic 0, and the third input node (Di) is at logic 1 when the fifth input node (R1) is triggered by the reload signal, the positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- 20 (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- 25 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and
- (e) if the reset signal received on the fourth input node (Rs) is at logic 1, the first output node (Fo) outputs a logic 0 signal; and, additionally, if the second input node (Mi) is also at logic 1, the second output node (Mo) outputs a logic 1

signal.

Claim 34 (original): The programmable frequency divider of claim 32, wherein each cell of the seventh type operates such that:

- 5 (a) regardless of the logic level of the second output node (Mo), if the third input node (Di) is at logic 0 when the fifth input node (R1) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 10 (b) if the second output node (Mo) is at logic 1 and the third input node (Di) is at logic 1 when the fifth input node (R1) is triggered by the reload signal, the positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- 15 (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic signal as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output
20 node (Mo) outputs a logic 0 signal; and
- (e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal; and, additionally, if the second input node (Mi) is also at
25 logic 1, the second output node (Mo) outputs a logic 1 signal.

Claim 35 (original): The programmable frequency divider of claim 32, wherein the fifth input node (R1) of each cell of the seventh type

is coupled to the second output node (Mo) of the last cell of the seventh type in order to apply the result signal to be the reload signal.

5 Claim 36 (original): The programmable frequency divider of claim 32, further comprising a control circuit for providing the reset signal.

10 Claim 37 (original): The programmable frequency divider of claim 32, further comprising:
a cell of an eighth type having a bypass mode and being cascaded to the last cell of the seventh type, the cell of the eighth type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rs), a fifth
15 input node (Rl), a sixth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input node (Fi) being coupled to a first output node (Fo) of the last cell of the seventh type, the second input node (Mi) being coupled to Vcc, the third input node (Di) being
20 used for receiving a corresponding divisor signal, the fourth input node (Rs) being used for receiving the reset signal to reset the cell of the eighth type, the fifth input node (Rl) being used for receiving the reload signal to synchronously reload the corresponding divisor signal to the third input node (Di),
25 the sixth input node (Ci) being coupled to the last divisor signal, and the second output node (Mo) being coupled to the second input node (Mi) of the last cell of the seventh type;
wherein the reload signal triggers the cell of the eighth type to

synchronously reload the corresponding divisor signal to the third input node (Di) and the cell of the eighth type switches to a divide-by-two or a divide-by-three mode after being synchronously reset according to the divisor signal, and if the last divisor signal received on the sixth input node (Ci) is at a bypass-mode active state, the cell of the eighth type switches to a bypass mode.

Claim 38 (original): The programmable frequency divider of claim 37, wherein each cell of the eighth type operates such that:

- (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0, and the third input node (Di) is at logic 0 when the fifth input node (Ri) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fifth input node (Ri) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi),

if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal;

(e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal; and

(f) if the signal received on the sixth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal.

Claim 39 (original): The programmable frequency divider of claim 37, wherein the fifth input node (Rl) is coupled to the second output node (Mo) of the last cell of the seventh type in order to apply the result signal to be the reload signal.

Claim 40 (currently amended): The programmable frequency divider of claim 37, further comprising:

at least one cell of a ninth type having a bypass mode and being cascaded between at least one cell of the seventh type and the cell of the eighth type, each cell of the ninth type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rs), a fifth input node (Rl), a sixth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the ninth type, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell,

the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Rs) being used for receiving the reset signal to synchronously reset the cell of the ninth type, the fifth input node (Rl) being used for receiving the reload signal to synchronously reload the ~~corresponding~~ corresponding divisor signal to the third input node (Di), the sixth input node (Ci) being coupled to a third output node (Co) of the subsequent cell and being used for receiving a bypass-mode enabling signal, a first input node (Fi) of a first cell of the ninth type being coupled to the first output node (Fo) of the last cell of the seventh type, a second output node (Mo) of the first cell of the ninth type being coupled to the second input node (Mi) of the last cell of the seventh type, a first output node (Fo) of a last cell of the ninth type being coupled to the first input node (Fi) of the cell of the eighth type, and a second input node (Mi) of the last cell of the ninth type being coupled to the second output node (Mo) of the cell of the eighth type;

wherein the reload signal triggers the at least one cell of the ninth type to synchronously reload the corresponding divisor signal to the third input node (Di) and each cell of the ninth type switches to a divide-by-two or divide-by-three mode after being synchronously reset according to the respective divisor signal, and if the bypass-mode enabling signal received on the sixth input node (Ci) is at an active state, the cell of the ninth type switches to a bypass mode.

Claim 41 (original): The programmable frequency divider of claim 40,

wherein each cell of the ninth type operates such that:

- 5 (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fifth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 10 (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fifth input node (Rl) triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a
15 one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- 20 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal;
- (e) if the reset signal received on the fourth input node (Rs) is enabled, the first output node (Fo) outputs a logic 0 signal; and, additionally, if the second input node (Mi) is also at
25 logic 1, the second output node (Mo) outputs a logic 1 signal; and
- (f) if the bypass-mode enabling signal received on the sixth input node (Ci) is at an active state, the first output node

(Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal.

5 Claim 42 (original): The programmable frequency divider of claim 40, wherein the fifth input node (R1) of each cell of the ninth type is coupled to the second output node (Mo) of the last cell of the seventh type in order to apply the result signal to be the reload signal.

10 Claim 43 (cancelled)

Claim 44 (currently amended): A programmable frequency divider for dividing frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the
15 programmable frequency divider comprising:
at least one cell of a tenth type being switchable between divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a
20 first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding divisor signal, and the first input node (Fi) of a first cell of the tenth type being coupled to the source signal; and
a cell of an eleventh type having a first input node (Fi), a second
25 input node (Mi), a third input node (Di), a fourth input node (R1), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input node (Fi) being coupled to a first output node (Fo) of a last

cell of the tenth type, the second input node (Mi) being set to logic 1, the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Ri) being used for receiving a reload signal to synchronously reload the
5 ~~corresponding divisor~~ corresponding divisor signal to the third input node (Di), the fifth input node (Ci) being coupled to a last divisor signal, and the second output node (Mo) being coupled to a second input node (Mi) of the last cell of the tenth type;

10 wherein if the programmable frequency divider comprising a plurality of cells of the tenth type, the cells of the tenth type being cascaded with each other and each cell of the tenth type, the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the tenth type, the second input
15 node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the tenth type; the programmable frequency divider selectively switches each cell to a divide-by-two or a divide-by-three mode according to the respective divisor signal, the reload signal triggers the third input node (Di) of
20 the cell of the eleventh type to reload the corresponding divisor signal, if the last divisor signal received in the fifth input node (Ci) of the cell of the eleven type is at a bypass-mode active state, the cell of the eleventh type switches to a bypass mode, and the second output node (Mo) or
25 the first output node (Fo) of the last cell of the tenth type outputs the result signal having the divided frequency; each cell of the tenth type operates such that:

(a) regardless of the logic level of the second input node (Mi),

- if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 5 (b) if the second input node (Mi) is at logic 1, the first output node (Fo) is at logic 0, and the third input node (Di) is at logic 1, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- 10 (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi); and
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal.
- 15

Claim 45 (previously presented): A programmable frequency divider for dividing frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the

20 programmable frequency divider comprising:

at least one cell of a tenth type being switchable between divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a

25 first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding divisor signal, and the first input node (Fi) of a first cell of the tenth type being coupled to the source signal; and

5 a cell of an eleventh type having a first input node (Fi), a second
input node (Mi), a third input node (Di), a fourth input node
(Rl), a fifth input node (Ci), a first output node (Fo), a second
output node (Mo), and a third output node (Co), the first input
node (Fi) being coupled to a first output node (Fo) of a last
cell of the tenth type, the second input node (Mi) being set to
logic 1, the third input node (Di) being used for receiving a
corresponding divisor signal, the fourth input node (Rl) being
used for receiving a reload signal to synchronously reload the
10 corresponding divisor signal to the third input node (Di), the
fifth input node (Ci) being coupled to a last divisor signal, and
the second output node (Mo) being coupled to a second input
node (Mi) of the last cell of the tenth type;
15 wherein if the programmable frequency divider comprising a
plurality of cells of the tenth type, the cells of the tenth type
being cascaded with each other and each cell of the tenth type,
the first output node (Fo) being coupled to a first input node
(Fi) of a subsequent cell of the tenth type, the second input
node (Mi) being coupled to a second output node (Mo) of the
20 subsequent cell of the tenth type; the programmable frequency
divider selectively switches each cell to a divide-by-two or a
divide-by-three mode according to the respective divisor
signal, the reload signal triggers the third input node (Di) of
the cell of the eleventh type to reload the corresponding
divisor signal, if the last divisor signal received in the fifth
input node (Ci) of the cell of the eleven type is at a
25 bypass-mode active state, the cell of the eleventh type
switches to a bypass mode, and the second output node (Mo) or

the first output node (Fo) of the last cell of the tenth type outputs the result signal having the divided frequency; each cell of the tenth type operates such that:

- 5 (a) regardless of the logic level of the second output node (Mo), if the third input node (Di) is at logic 0, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 10 (b) if the second output node (Mo) and the third input node (Di) are both at logic 1, the positive edge of the clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi); and
- 15 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal.

20 Claim 46 (currently amended): A programmable frequency divider for dividing frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the programmable frequency divider comprising:

25 at least one cell of a tenth type being switchable between divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding

divisor signal, and the first input node (Fi) of a first cell of the tenth type being coupled to the source signal; and

5 a cell of an eleventh type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rl), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input node (Fi) being coupled to a first output node (Fo) of a last cell of the tenth type, the second input node (Mi) being set to logic 1, the third input node (Di) being used for receiving a
10 corresponding divisor signal, the fourth input node (Rl) being used for receiving a reload signal to synchronously reload the ~~corresponding divisor~~ corresponding divisor signal to the third input node (Di), the fifth input node (Ci) being coupled to a last divisor signal, and the second output node (Mo) being
15 coupled to a second input node (Mi) of the last cell of the tenth type;

wherein if the programmable frequency divider comprising a plurality of cells of the tenth type, the cells of the tenth type being cascaded with each other and each cell of the tenth type,
20 the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the tenth type, the second input node (Mi) being coupled to a second output node (Mo) of the subsequent cell of the tenth type; the programmable frequency divider selectively switches each cell to a divide-by-two or a
25 divide-by-three mode according to the respective divisor signal, the reload signal triggers the third input node (Di) of the cell of the eleventh type to reload the corresponding divisor signal, if the last divisor signal received in the fifth

input node (Ci) of the cell of the eleven type is at a bypass-mode active state, the cell of the eleventh type switches to a bypass mode, and the second output node (Mo) or the first output node (Fo) of the last cell of the tenth type outputs the result signal having the divided frequency;-the cell of the eleventh type operates such that:

- (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and
- (e) if the signal received on the fifth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0

signal and the second output node (Mo) outputs a logic 1 signal.

5 Claim 47 (currently amended): A programmable frequency divider for dividing frequency of a source signal according to a selectable divisor which is obtained based on a plurality of divisor signals and outputting a result signal having a divided frequency, the programmable frequency divider comprising:
10 at least one cell of a tenth type being switchable between divide-by-two and divide-by-three modes having a first input node (Fi), a second input node (Mi), a third input node (Di), a first output node (Fo), and a second output node (Mo), the third input node (Di) being used for receiving a corresponding divisor signal, and the first input node (Fi) of a first cell of the
15 tenth type being coupled to the source signal; and
a cell of an eleventh type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Ri), a fifth input node (Ci), a first output node (Fo), a second output node (Mo), and a third output node (Co), the first input
20 node (Fi) being coupled to a first output node (Fo) of a last cell of the tenth type, the second input node (Mi) being set to logic 1, the third input node (Di) being used for receiving a corresponding divisor signal, the fourth input node (Ri) being used for receiving a reload signal to synchronously reload the
25 ~~corresponding divisor~~ corresponding divisor signal to the third input node (Di), the fifth input node (Ci) being coupled to a last divisor signal, the second output node (Mo) being coupled to a second input node (Mi) of the last cell of the tenth type;

and the fourth input node (Rl)-is being coupled to the second output node (Mo) of the last cell of the tenth type in order to apply the result signal to be the reload signal;

5 wherein if the programmable frequency divider comprising a plurality of cells of the tenth type, the cells of the tenth type being cascaded with each other and each cell of the tenth type, the first output node (Fo) being coupled to a first input node (Fi) of a subsequent cell of the tenth type, the second input node (Mi) being coupled to a second output node (Mo) of the
10 subsequent cell of the tenth type; the programmable frequency divider selectively switches each cell to a divide-by-two or a divide-by-three mode according to the respective divisor signal, the reload signal triggers the third input node (Di) of the cell of the eleventh type to reload the corresponding
15 divisor signal, if the last divisor signal received in the fifth input node (Ci) of the cell of the eleven type is at a bypass-mode active state, the cell of the eleventh type switches to a bypass mode, and the second output node (Mo) or the first output node (Fo) of the last cell of the tenth type
20 outputs the result signal having the divided frequency.

Claim 48 (previously presented): The programmable frequency divider of claim 47, further comprising:

25 at least one cell of a twelfth type being cascaded between at least one cell of the tenth type and the cell of the eleventh type, and each cell of the twelfth type having a first input node (Fi), a second input node (Mi), a third input node (Di), a fourth input node (Rl), a fifth input node (Ci), a first output node

(Fo), a second output node (Mo), and a third output node (Co),
the first output node (Fo) being coupled to a first input node
(Fi) of a subsequent cell of the twelfth type, the second input
node (Mi) being coupled to a second output node (Mo) of the
5 subsequent cell, the third input node (Di) being used for
receiving a corresponding divisor signal, the fourth input node
(Ri) being used for receiving the reload signal to
synchronously reload the corresponding divisor signal to the
third input node (Di), the fifth input node (Ci) being coupled
10 to a third output node (Co) of the subsequent cell and being
used for receiving a bypass-mode enabling signal, a first input
node (Fi) of a first cell of the twelfth type being coupled to the
first output node (Fo) of the last cell of the tenth type, a
second output node (Mo) of the first cell of the twelfth type
15 being coupled to the second input node (Mi) of the last cell of
the tenth type, a first output node (Fo) of a last cell of the
twelfth type being coupled to the first input node (Fi) of the
cell of the eleventh type, and a second input node (Mi) of the
last cell of the twelfth type being coupled to the second output
20 node (Mo) of the cell of the eleventh type;
wherein the reload signal triggers each cell of the twelfth type to
synchronously reload the corresponding divisor signal to the
third input node (Di), each cell of the twelfth type switches to
a divide-by-two or divide-by-three mode according to the
25 loaded divisor signal, and if the bypass-mode enabling signal
received on the fifth input node (Ci) is at an active state, the
cell of the twelfth type switches to a bypass mode.

Claim 49 (original): The programmable frequency divider of claim 48, wherein each cell of the twelfth type operates such that:

- 5 (a) regardless of the logic level of the second input node (Mi) or the second output node (Mo), if the first output node (Fo) is at logic 0 and the third input node (Di) is at logic 0 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of a clock signal of the first input node (Fi) triggers the first output node (Fo) to output a half frequency signal;
- 10 (b) if the first output node (Fo) is at logic 0, the second input node (Mi) is at logic 1 (or if the second output node (Mo) is at logic 1), and the third input node (Di) is at logic 1 when the fourth input node (Rl) is triggered by the reload signal, the positive edge of the clock signal of the first input node
- 15 (Fi) triggers the first output node (Fo) to output a one-third-frequency signal;
- (c) if the first output node (Fo) is at logic 0, the second output node (Mo) outputs a signal at the same logic level as the second input node (Mi);
- 20 (d) regardless of the logic level of the second input node (Mi), if the first output node (Fo) is at logic 1, the second output node (Mo) outputs a logic 0 signal; and
- 25 (e) if the bypass-mode enabling signal received on the fifth input node (Ci) is at an active state, the first output node (Fo) outputs a logic 0 signal and the second output node (Mo) outputs a logic 1 signal.

Claim 50 (original): The programmable frequency divider of claim 48,

wherein the fourth input node (R1) of each cell of the twelfth type is coupled to the second output node (Mo) of the last cell of the tenth type in order to apply the result signal to be the reload signal.

5

Claim 51 (cancelled)